Nanopartz Inc.

SAFETY DATA SHEET

Version 1.0 Revision Date 01/21/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Gold nanoparticles in Toluene

Product Number : E and B product families in toluene

Brand : Nanopartz

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Nanopartz Inc.

146 Barberry Pl. Loveland CO 80537

Telephone : +1 844-334-5555 Fax : +1 866-811-6266

1.4 Emergency telephone number

Emergency Phone # : +1-844-334-5555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315

Reproductive toxicity (Category 2), H361

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Specific target organ toxicity - repeated exposure (Category 2), H373

Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

| Precautionary statement(s) | |
|----------------------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and |
| | understood. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| P264 | Wash skin thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face |
| | protection. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. |
| | Rinse skin with water/shower. |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for |
| | breathing. Call a POISON CENTER/doctor if you feel unwell. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P331 | Do NOT induce vomiting. |
| P332 + P313 | If skin irritation occurs: Get medical advice/ attention. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula : Au in C₇H₈

Molecular weight : 92.14 g/mol
CAS-No. : 108-88-3
EC-No. : 203-625-9
Index-No. : 601-021-00-3

Registration number : 01-2119471310-51-XXXX

Hazardous components

| Component | Classification | Concentration |
|-----------|--|---------------|
| Toluene | | |
| | Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; H225, H304, H315, H336, H361, H373, H401 | 90 - 100 % |

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis | | | |
|-----------|----------|---|----------------------|---|--|--|--|
| Toluene | 108-88-3 | TWA | 100 ppm 375 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 | | | |
| | | STEL | 150 ppm 560 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 | | | |
| | | TWA | 200 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 | | | |
| Rem | Remarks | Z37.12-1967 | | | | | |
| | | CEIL | 300 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 | | | |
| | | Z37.12-19 | Z37.12-1967 | | | | |
| | | Peak | 500 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 | | | |
| | | Z37.12-19 | 67 | | | | |
| | | TWA | 20 ppm | USA. ACGIH Threshold Limit Values (TLV) | | | |
| | | Visual impairment Female reproductive Pregnancy loss 2015 Adoption Substances for which there is a Biological Exposure Index or (see BEI® section) Not classifiable as a human carcinogen | | | | | |
| | | TWA | 100 ppm 375 mg/m3 | USA. NIOSH Recommended Exposure Limits | | | |
| | | ST | 150 ppm 560 mg/m3 | USA. NIOSH Recommended Exposure Limits | | | |

Biological occupational exposure limits

| Biological occupati | | , | | | |
|---------------------|----------|--|---------------|------------|--------------------|
| Component | CAS-No. | Parameters | Value | Biological | Basis |
| | | | | specimen | |
| | | | | | |
| Toluene | 108-88-3 | Toluene | 0.0200 | In blood | ACGIH - Biological |
| | | | mg/l | | Exposure Indices |
| | | | | | (BEI) |
| | Remarks | Prior to last sh | ift of workwe | ek | |
| | | Toluene | 0.0300 | Urine | ACGIH - Biological |
| | | | mg/l | | Exposure Indices |
| | | | | | (BEI) |
| | | End of shift (As soon as possible after exposure ceases) | | | |
| | | o-Cresol | 0.3000 | Urine | ACGIH - Biological |
| | | | mg/g | | Exposure Indices |
| | | | | | (BEI) |
| | | End of shift (As soon as possible after exposure ceases) | | | |
| | | Toluene | 0.02 mg/l | In blood | ACGIH - Biological |
| | | | | | Exposure Indices |
| | | | | | (BEI) |
| | | Prior to last shift of workweek | | | |

| Toluene | 0.03 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
|--|-----------------------|-------|---|
| End of shift (As soon as possible after exposure ceases) | | | |
| o-Cresol | 0.3mg/g Creatinine | Urine | ACGIH - Biological Exposure Indices (BEI) |
| End of shift (As soon as possible after exposure ceases) | | | |

Derived No Effect Level (DNEL)

| Derived No Lifect Level (DNLL) | | | | | |
|--------------------------------|--------------|----------------------------|----------------|--|--|
| Application Area | Exposure | Health effect | Value | | |
| | routes | | | | |
| Workers | Inhalation | Acute systemic effects | 384 mg/m3 | | |
| Workers | Inhalation | Acute local effects | 384 mg/m3 | | |
| Workers | Skin contact | Long-term systemic effects | 384mg/kg BW/d | | |
| Workers | Inhalation | Long-term systemic effects | 192 mg/m3 | | |
| Workers | Inhalation | Long-term local effects | 192 mg/m3 | | |
| Consumers | Inhalation | Acute systemic effects | 226 mg/m3 | | |
| Consumers | Inhalation | Acute local effects | 226 mg/m3 | | |
| Consumers | Skin contact | Long-term systemic effects | 226mg/kg BW/d | | |
| Consumers | Inhalation | Long-term systemic effects | 56.5 mg/m3 | | |
| Consumers | Ingestion | Long-term systemic effects | 8.13mg/kg BW/d | | |

Predicted No Effect Concentration (PNEC)

| Compartment | Value | |
|------------------------------|-------------|--|
| Soil | 2.89 mg/kg | |
| Marine water | 0.68 mg/l | |
| Fresh water | 0.68 mg/l | |
| Marine sediment | 16.39 mg/kg | |
| Fresh water sediment | 16.39 mg/kg | |
| Sewage treatment plant | 13.61 mg/l | |
| Aquatic intermittent release | 0.68 mg/l | |

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Colour: colourless

b) Odour aromatic

c) Odour Threshold No data availabled) pH No data available

e) Melting point/freezing

point

Melting point/range: -93 °C (-135 °F)

f) Initial boiling point and 110 - 111

boiling range

110 - 111 °C (230 - 232 °F)

g) Flash point 4.0 °C (39.2 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, gas) No data available

j) Upper/lower Upper explosion limit: 7 %(V) flammability or Lower explosion limit: 1.2 %(V)

explosive limits

k) Vapour pressure 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)

I) Vapour density No data available

m) Relative density 0.865 g/mL at 25 °C (77 °F)

n) Water solubility 0.5 g/l at 15 °C (59 °F)

o) Partition coefficient: n-

octanol/water

No data available

p) Auto-ignition 535.0 °C (995.0 °F) temperature

q) Decomposition No data available temperature

r) Viscosity No data available
 s) Explosive properties No data available
 t) Oxidizing properties No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - > 5,580 mg/kg

LC50 Inhalation - Rat - 4 h - 12,500 - 28,800 mg/m3

LD50 Dermal - Rabbit - 12,196 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation - 24 h

Serious eye damage/eye irritation

Eves - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

Rat

Liver

DNA damage

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Damage to fetus possible

Suspected human reproductive toxicant

Reproductive toxicity - Rat - Inhalation

Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Developmental Toxicity - Rat - Oral

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: XS5250000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h

NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h

Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h

EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

12.2 Persistence and degradability

Biodegradability Result: - Readily biodegradable.

12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d

- 0.05 mg/l

Bioconcentration factor (BCF): 90

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1294 Class: 3 Packing group: II

Proper shipping name: Toluene Reportable Quantity (RQ): 1000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1294 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: TOLUENE

IATA

UN number: 1294 Class: 3 Packing group: II

Proper shipping name: Toluene

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

 CAS-No.
 Revision Date

 Toluene
 108-88-3
 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

CAS-No. Revision Date
Toluene 108-88-3 2007-07-01

Pennsylvania Right To Know Components

Toluene CAS-No. Revision Date 108-88-3 2007-07-01

New Jersey Right To Know Components

CAS-No. Revision Date
Toluene 108-88-3 2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the CAS-No. Revision Date State of California to cause birth defects or other reproductive 108-88-3 2009-02-01

harm. Toluene

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Acute aquatic toxicity
Asp. Tox. Aspiration hazard
Flam. Lig. Flammable liquids

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life. Repr. Reproductive toxicity

Skin Irrit. Skin irritation

HMIS Rating

Health hazard: 2

Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating
Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0